

SAFETY DATA SHEET

Page 1 of 2

TYRE DUSTING CHALK

Revision 0
Revision date

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product name TYRE DUSTING CHALK
Company GreSolvent
Unit C1A
Wem Industrial Estate
Soulton Road
Wem
Shropshire
SY4 5SD
England
Telephone +44 (0)1939 232326
Fax +44 (0)1939 232386

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients

	Conc.	CAS	EINECS	Symbols/Risk phrases
Talc (Hydrous Magnesium Silicate) (Talc, respirable dust)	90 - 100%	14807-96-6		

3. HAZARDS IDENTIFICATION

Main hazards No Significant Hazard

4. FIRST AID MEASURES

Skin contact May cause irritation to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.

Eye contact May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.

Inhalation May cause irritation to mucous membranes. Move the exposed person to fresh air.

Ingestion May cause irritation to mucous membranes. DO NOT INDUCE VOMITING. Seek medical attention if irritation or symptoms persist.

5. FIRE FIGHTING MEASURES

Extinguishing media Use extinguishing media appropriate to the surrounding fire conditions.

Fire hazards Burning produces irritating, toxic and obnoxious fumes.

Protective equipment Wear suitable respiratory equipment when necessary.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions Ensure adequate ventilation of the working area.

Environmental precautions Do not allow product to enter drains. Prevent further spillage if safe.

Clean up methods Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

Print date 18-May-2007

TYRE DUSTING CHALK

Revision 0
Revision date

7. HANDLING AND STORAGE

Handling	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.
Storage	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits

Talc (Hydrous Magnesium Silicate)
(Talc, respirable dust)

WEL 8-hr limit ppm: -
WEL 15 min limit ppm: -

WEL 8-hr limit mg/m3: 1
WEL 15 min limit mg/m3: -

Engineering measures	Ensure adequate ventilation of the working area.
Hand protection	Chemical resistant gloves (PVC)
Eye protection	In case of splashing, wear: Approved safety goggles.
Protective equipment	Wear protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Description	Powder.
Colour	White.
Odour	Odourless.
pH	7
Water solubility	insoluble in water.

10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
------------------	---------------------------------

11. TOXICOLOGICAL INFORMATION

Toxicological information	No known adverse health effects.
----------------------------------	----------------------------------

12. ECOLOGICAL INFORMATION

Ecotoxicity	No known adverse environmental effects.
--------------------	---

13. DISPOSAL CONSIDERATIONS

General information	Dispose of in compliance with all local and national regulations.
----------------------------	---

14. TRANSPORT INFORMATION

Further information	The product is not classified as dangerous for carriage.
----------------------------	--

15. REGULATORY INFORMATION

Labelling	Non hazardous.
------------------	----------------

Risk phrases

16. OTHER INFORMATION

Further information	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
----------------------------	--