# SAFETY DATA SHEET

Page 1 of 3

0

# PENETRATING OIL

Revision

Revision date

## 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product name PENETRATING OIL

Company GreSolvent

Unit C1A

Wem Industrial Estate

Soulton Road

Wem Shropshire SY4 5SD England

enquiries@gresolvent.co.uk WWW.GRESOLVENT.CO.UK

**Telephone** +44 (0)1939 232326 **Fax** +44 (0)1939 232386

## 2. COMPOSITION / INFORMATION ON INGREDIENTS

#### Hazardous ingredients

	Conc.	CAS	EINECS	Symbols/Risk phrases
Kerosine - unspecified - distillates (petroleum), hydrotreated light	90 - 100%	64742-47-8	265-149-8	Xn; R65
Special Boiling Point Spirit 100/140	1 - 10%	64742-49-0	265-151-9	F;R11 Xi;R38 N;R51/53 Xn;R65

## 3. HAZARDS IDENTIFICATION

Main hazards Harmful: may cause lung damage if swallowed.

## 4. FIRST AID MEASURES

**Skin contact** May cause irritation to skin. May cause dermatitis. Wash off immediately with plenty of

soap and water. Remove contaminated clothing. Seek medical attention if irritation or

symptoms persist.

**Eye contact** May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes

holding the eyelids open. Seek medical attention if irritation or symptoms persist.

Inhalation Harmful by inhalation. Inhalation may cause nausea and vomiting. May cause dizziness

and headache. Move the exposed person to fresh air. Seek medical attention.

**Ingestion** Harmful if swallowed. Ingestion may cause nausea and vomiting. Ingestion is irritating

to the respiratory tract and may cause damage to the central nervous system. DO NOT INDUCE VOMITING. If swallowed, seek medical advice immediately and show this

container or label.

#### 5. FIRE FIGHTING MEASURES

**Extinguishing media** Use as appropriate: carbon dioxide (CO2), dry chemical, foam.

**Fire hazards** Burning produces irritating, toxic and obnoxious fumes.

**Protective equipment** Self-contained breathing apparatus. Wear protective clothing.

Print date 28-Nov-2007

# PENETRATING OIL

Revision 0
Revision date

## **6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions** Ensure adequate ventilation of the working area. Wear suitable protective equipment.

Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

Clean up methods

Absorb with inert, absorbent material. Transfer to suitable, labelled containers for

disposal. Clean spillage area thoroughly with plenty of water.

## 7. HANDLING AND STORAGE

**Handling** Avoid contact with eyes and skin. Ensure adequate ventilation of the working area.

Adopt best Manual Handling considerations when handling, carrying and dispensing.

**Storage** Keep in a cool, dry, well ventilated area. Keep containers tightly closed.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Engineering measures** Ensure adequate ventilation of the working area.

**Respiratory protection** Self-contained breathing apparatus. Wear protective clothing.

**Hand protection** Chemical resistant gloves (PVC)

**Eye protection** Approved safety goggles.

**Protective equipment** Wear chemical protective clothing.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

DescriptionLiquid.ColourColourless.OdourSlight.

Water solubility miscible in water.

## 10. STABILITY AND REACTIVITY

**Stability** Stable under normal conditions.

## 11. TOXICOLOGICAL INFORMATION

**Toxicological information** No data is available on this product.

Special Boiling Point Spirit 100/140 Oral Rat LD50 = >2000mg/kg

#### 12. ECOLOGICAL INFORMATION

**Ecotoxicity** No data is available on this product.

## 13. DISPOSAL CONSIDERATIONS

**General information** Dispose of in compliance with all local and national regulations.

# PENETRATING OIL

Revision 0
Revision date

## 14. TRANSPORT INFORMATION

ADR/RID

UN 1223 Packing group III
Class 3 Hazard ID 30

Proper Shipping KEROSENE BASED Name PENETRATING OIL.

**IMDG** 

UN 1223 Packing group III
Class 3 Marine pollutant NO

EmS Code F-E S-E

**IATA** 

UN 1223 Packing group |||
Class 3 Subsidiary risk Maximum quantity 220 L

Packing Instruction 310 Maximum quantity 220 L (Cargo)

Packing Instruction 309 Maximum quantity 60 L

(Passenger)

## 15. REGULATORY INFORMATION

**Labelling** The product is classified in accordance with 67/548/EEC.

Symbols Xn - Harmful



**Risk phrases** R65 - Harmful: may cause lung damage if swallowed.

Safety phrases S62 - If swallowed, do not induce vomiting: seek medical advice immediately and show

this container or label.

#### **16. OTHER INFORMATION**

Text of risk phrases in Section 2

R11 - Highly flammable. R38 - Irritating to skin.

R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R65 - Harmful: may cause lung damage if swallowed.

**Further information**The information supplied in this Safety Data Sheet is designed only as guidance for the

safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. As the application of products is outside our control, the information is given without legal resposibility. Customers should test under their own conditions to ensure

the products are suitable for their own requirements.