## SAFETY DATA SHEET

## RIMSEAL

Page 1 of 3

0

Revision Revision date

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY					
Product name	RIMSEAL				
Company	GreSolvent Unit C1A Wem Industrial Soulton Road Wem Shropshire SY4 5SD England	Estate			
Telephone	+44 (0)1939 23	2326			
Fax	+44 (0)1939 23	2386			
2. COMPOSITION / INFORMATION ON INGREDIENTS					
Hazardous ingredients					
Talc (Hydrous Magnesium Silicate)		<b>Conc.</b> 1 - 10%	<b>CAS</b> 14807-96-6	EINECS	Symbols/Risk phrases
(Talc, respirable dust) C9-11 Alcohol Ethoxylate with 8Me	0	1 - 10%	68439-45-2		Xn;R22 Xi;R41
Sodium hydroxide		0 - 0.5%	1310-73-2	215-185-5	C; R35
3. HAZARDS IDENTIFICATION					
Main hazards	No Significant Hazard				
4. FIRST AID MEASURES					
Skin contact	May cause irritation to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.				
Eye contact	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.				
Inhalation	May cause irritation to mucous membranes. Move the exposed person to fresh air.				
Ingestion	May cause irritation to mucous membranes. DO NOT INDUCE VOMITING. Seek medical attention if irritation or symptoms persist.				
5. FIRE FIGHTING MEASURES					
Extinguishing media	Use extinguishing media appropriate to the surrounding fire conditions.				
Fire hazards	Burning produces irritating, toxic and obnoxious fumes.				
Protective equipment	Wear suitable respiratory equipment when necessary.				

0

## RIMSEAL

Revision Revision date

		Revision date			
6. ACCIDENTAL RELEASE	MEASURES				
Personal precautions	Ensure adequate ventilation of the working area.				
Environmental precautions	Do not allow product to enter drains. Prevent further spillage if safe.				
Clean up methods	Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.				
7. HANDLING AND STORAGE					
Handling	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area.				
Storage	Adopt best Manual Handling considerations when handling, carrying and dispensing. Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in				
Storage	correctly labelled containers.				
8. EXPOSURE CONTROLS	/ PERSONAL PROTECTION				
Exposure limits					
Talc (Hydrous Magnesium Silicate)	) WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: 1			
(Talc, respirable dust)	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -			
Sodium hydroxide	WEL 8-hr limit ppm: - WEL 15 min limit ppm: -	WEL 8-hr limit mg/m3: - WEL 15 min limit mg/m3: 2			
Engineering measures	Ensure adequate ventilation of the working area.				
Hand protection	Chemical resistant gloves (PVC)				
Eye protection	In case of splashing, wear: Approved safety goggles.				
Protective equipment	Wear protective clothing.				
9. PHYSICAL AND CHEMICAL PROPERTIES					
Description	Paste.				
Colour	Brown.				
Odour	Characteristic.				
Water solubility	insoluble in water.				
10. STABILITY AND REAC	ΤΙVITY				
Stability	Stable under normal conditions.				
11. TOXICOLOGICAL INFO	RMATION				
Toxicological information	No known adverse health effects.				
12. ECOLOGICAL INFORMATION					
Ecotoxicity	No known adverse environmental effects.				
13. DISPOSAL CONSIDER	ATIONS				
General information	Dispose of in compliance with all local and national regulations.				
14. TRANSPORT INFORMATION					
Further information	The product is not classifed as dangerous for carriage.				
15. REGULATORY INFORM	IATION				

**Risk phrases** 

0

## RIMSEAL

Revision Revision date

16. OTHER INFORMATIO	N
Text of risk phrases in Section 2	R22 - Harmful if swallowed. R35 - Causes severe burns. R41 - Risk of serious damage to eyes.
Further information	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. As the application of products is outside our control, the information is given without legal resposibility. Customers should test under their own conditions to ensure the products are suitable for their own requirements.
Labelling for contents	>= 15% - < 30% : soap.